



### Dodge Truck Carburetor ETW1 with Governor—List Price \$50.40

WHEN SERVICING, USE GASKET ASSORTMENT No. 678, PRICE \$0.81; CARB. REPAIR PACKAGE No. 1341, PRICE \$7.28; GOVERNOR REPAIR PACKAGE No. 5500, PRICE \$4.41.

PART NAMES IN BOLD TYPE, LISTED BELOW, INDICATE CONTENTS OF CARBURETOR REPAIR PACKAGE  
PART NAMES KEYED WITH † INDICATE CONTENTS OF GOVERNOR REPAIR PACKAGE

Part No.	PART NAME	List Price	Part No.	PART NAME	List Price
1-432S	Body flange and governor assembly.....	\$23.52	86-11	Body flange screw lock washer.....(3)	.02
1A-31	†Flange gasket.....	.08	86-15	Flange stud lock washer.....(2)	.02
4-475S	Throttle lever assembly.....	.74	86-16	Choke valve screw lock washer.....(2)	.02
6-502S	Air horn assembly.....	6.99	86-41	Choke and throttle valve screw lock washer (Sup. by 86-16).....(2)	.02
7-134S	Choke valve assembly (Sup. by 7-138S).....	.74	86-46	†Governor throttle shaft lock washer.....	.04
7-138S	Choke valve assembly.....	.74	101-10	Wire clamp screw.....	.07
11B-17	XPump discharge passage plug.....	.15	101-142S	Choke bracket screw and washer assembly.....	.07
11B-41	Rivet plug.....(3)	.03	101-150S	Air horn screw and washer assembly.....(3)	.07
11B-69	Rivet plug.....(3)	.03	101-160S	†Governor housing plate cover screw and washer assembly.....(4)	.07
11B-79	Rivet plug.....	.03	101-171	Throttle lever clamp screw.....	.07
11B-103	Main vent tube rivet plug (Sup. by 11B-220).....	.03	101-172	†Governor housing attaching screw.....(3)	.04
11B-108	Idle port rivet plug.....	.03	101-173	Choke valve screw.....(2)	.07
11B-138	XPump jet rivet plug.....	.07	101-178	Headless screw.....	.07
11B-186S	†Governor adj. screw passage plug assembly.....	.45	101-179	Body flange attaching screw (3 cross holes).....	.22
11B-194	Pipe plug (1/2").....	.15	101-181	Throttle lever adjusting screw.....	.07
11B-220	Main vent tube rivet plug.....	.03	101-191	Body flange screw (2 cross holes).....	.36
14-328S	Choke control lever and shaft assembly.....	.59	101-195	Body flange screw (2 cross holes).....	.22
20-26	*Main metering jet gasket.....	.07	101-199S	Air horn screw and washer assembly (hex head).....(2)	.22
20-31	Needle seat gasket.....	.07	101-200S	†Governor housing plate cover screw and washer assembly.....	.22
20-35	*Governor adj. screw passage plug gasket.....	.07	101-203	†Governor adjusting screw.....	.45
20-51	*Step-up jet gasket.....	.07	105-11	Tube clamp screw.....	.07
20-52	Step-up piston gasket.....	.07	105A-8	Tube clamp nut.....	.07
21-91S	Float and lever assembly.....	1.83	105A-13	Flange stud nut.....(2)	.07
24-23	Float lever pin.....	.07	105A-35	†Governor throttle shaft nut.....	.07
25-77S	Needle and seat assembly.....	1.18	116-13	Pump intake check ball.....	.03
25-116S	Needle and seat assembly (Sup. by 25-77S).....	1.18	116-18	Pump discharge check ball.....	.07
30A-44	Idle adjustment screw.....	.45	118-53S	Governor housing cover assembly with lever	6.62
38A-52S	†Governor adjusting screw bushing assembly (Brass).....	.88	121-104	Main body gasket.....	.15
38A-54S	†Governor adjusting screw bushing assembly (Die Cast).....	.88	121-113	†Governor housing cover assembly with lever	6.62
48-73	Pump jet.....	.29	121-114	†Body flange gasket.....	.08
61-84	Idle adjustment screw spring.....	.07	121-115	†Air horn to air cleaner adaptor gasket.....	.15
61-119	Choke pull-back spring.....	.15	123-47S	Idle orifice tube and plug assembly.....	.29
61-135	Step-up piston spring.....	.07	136-82	Main vent tube and plug gasket.....	.04
61-157	Pump plunger spring.....	.15	145-51S	Main vent tube and plug assembly.....	.66
61-277	Pump check spring.....	.07	149-82S	Step-up jet and gasket assembly.....	.36
61-288	†Governor spring.....	.29	159-89S	Main metering jet and gasket assembly—standard.....	.45
62-77S	Choke tube bracket assembly.....	.74	160-78S	Step-up piston, plate and rod assembly.....	.59
63-24	Float lever pin retainer.....	.07	181-129S	†Governor cam assembly.....	.45
63-37	Pump retainer ring.....	.07	218-10	†Governor chain.....	.22
64-90S	Pump plunger rod and piston assembly.....	1.83			
76-34	†Screw lock wire.....(2)	.03			
76-35	Screw lock wire.....	.03			
80-46S	Governor housing assembly.....	6.62			
86-9	Throttle lever screw lock washer.....	.02			

\*Gaskets so marked must be soaked in 90 proof denatured alcohol for 15 minutes, installed on part and let dry before using.

X Early production uses 11B-138 pump jet rivet plug. Later production uses 11B-17 (screw type) pump jet plug.

NOTE—Small figures in parentheses indicate number of pieces used in carburetor. Where no figure is shown, only one is used.

**CARBURETOR**  
TRADE MARK REG. U. S. PAT. OFF.  
MARCA REGISTRADA



